

ACO ACCESS


INSTALLATION DRAWING



DRWG# XASH-DC

Hermelock Access Cover: Concrete

www.acoaus.com.au

For EN124 Class D 400kN**NOTES:**

1. Specific site conditions may require an increase in these dimensions or reinforcement. It is the customer's responsibility to ensure the concrete encasement is designed for the application. *Engineering advice may be required.*
2. A minimum concrete strength of 25MPa is recommended. The concrete should be vibrated to eliminate air pockets.
3. The finished level of the concrete surround must be flush with the top of the frame.
4. Expansion and crack control joints are recommended to protect the pit and the concrete surround. *Engineering advice may be required.*
5. Refer to ACO's latest installation instructions for complete details.

ACO ACCESS

SPECIFICATION CLAUSE

ACO Polycrete Pty Ltd
 134-140 Old Bathurst Road
 Emu Plains NSW 2750
 Tel: +61 2 4747 4000
 Fax: +61 2 4747 4060
 e: technical@acoaus.com.au

DRWG# XASH-DC

Hermelock Access Cover

www.acoaus.com.au

All access covers & frames are to be ACO Access Hermelock®. Covers are to be manufactured from anti-slip polyurethane with four bolts per cover. Glass reinforced frames are to contain a double hermetic seal (with a neoprene rubber seal ring)**.

The cover systems shall satisfy the requirements of EN-124, Load Class D. For sizes & part nos. refer to Drawing/Table No. _____*

* Please delete or complete where appropriate.

** Option