

TD300 4-Bolt Iron Slotted grate

Product Features



Certified to AS 3996 Load Class G (900kN)
(NATA endorsed load test reports available)



AS 3996 (Clause 3.3.7) compliant for bicycle tyre penetration resistance

- Recesses in grate fit around 'anti-shunt' lugs on the edge rail to prevent longitudinal movement
- Uses '4-bolt' locking system
- Suitable for use with TD300 channels (or H300SK channels)
- Manufactured from ductile iron to AS 1831 Grade 500-7



Specifications

The grate shall be ACO TD300 4-Bolt Iron Slotted grate with a bolted locking system as manufactured by ACO. This grate has an overall width of 338mm and overall length of 500mm. Slot widths measure at a maximum of 18mm.

Materials & Design


The grate shall be manufactured from ductile iron and have **minimum** properties and characteristics as follows:

- Recesses in grate fit around 'anti-shunt' lugs on the edge rail to prevent longitudinal movement
- Manufactured from ductile iron to AS 1831 Grade 500-7
- Certified to AS 3996 Load Class G (900kN)¹
- Meets AS 3996 (Clause 3.3.7)
- Intake area of 82,400mm² per half metre of grate

¹ NATA endorsed test reports available

For the specification of the ACO TraffikDrain channel system selected, click: <http://www.acoaus.com.au/infrastructure>

ACO INFRASTRUCTURE®
TD300 4-Bolt Iron Slotted grate



Description	Part No.	Length (mm)	Width (mm)	Weight (kg)
Bolted grate				
TD300 4-Bolt Iron Slotted (bolts included)	143344	500	338	10.5
Grate removal tool	01318	-	-	0.1
Replacement M10 x 40 bolt	2324	-	-	-

‘4-Bolt’ locking mechanism



ACO offers a 4-bolt locking solution for applications requiring more security. The four threaded stainless steel inserts in the PowerDrain channel body allow a 4-bolt grate to be bolted into the channel for ultimate stiffness and security. Tamper resistant bolts can also be used.

ACO Pty Ltd
Australia
Ph: 1300 765 226
www.acoinfrastructure.com.au
sales@acoaus.com.au



© October 2026 ACO Pty Ltd. All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions are suitable. ACO Polycrete Pty Ltd. pursues a policy of continuous product development and reserves the right to amend specifications without notice.